

13790510059

5

4

3

2

1

C±0.25

1.15±0.20

5.70±0.35

1.75±0.25

Pin 1

B±0.30

1.00±0.10

A±0.25

EST1013 H - 1*NP X - B - X

↑
羿通代码+间距

↑
PIN数

↑
X本色
B黑色
R红色
L蓝色
Y黄色
G绿色
C透明

↑
X普通
B带扣
C刺破
2L示意两侧带锁扣

↑
U超薄F防呆型
HV带高凸点
LC带低凸点,
K卡槽
E有耳
NE无耳

↑
X公胶壳
G母胶壳

H示意胶壳,
H后无数字默认材质V0
H后带数字2示意材质V2

Poles	A	B	C
2	1.00	4.60	3.00
3	2.00	5.60	4.00
4	3.00	6.60	5.00
5	4.00	7.60	6.00
6	5.00	8.60	7.00
7	6.00	9.60	8.00
8	7.00	10.60	9.00
9	8.00	11.60	10.00
10	9.00	12.60	11.00
11	10.00	13.60	12.00
12	11.00	14.60	13.00
13	12.00	15.60	14.00
14	13.00	16.60	15.00
15	14.00	17.60	16.00
16	15.00	18.60	17.00
20	19.00	22.60	21.00
22	21.00	24.60	23.00
26	25.00	28.60	27.00
30	29.00	32.60	31.00

■ SPECIFICATIONS

- Voltage rating:100V AC/DC;
- Current rating:1A AC/DC;
- Withstanding Voltage:500V AC/minute
- Temperature range:-20℃~+85℃
- Insulation resistance:500MΩ Min
- Contact resistance:30mΩ Max
- Material:PA66
- After environmental testing:40 mΩ Max

日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST1013H-1*NPX-X-X

品名 TITLE: 1013-H

材料:

单位:

MM

包装规格:

比例:

1:1

制图:


审核:

核准:

日期:

2025. 7. 11

一般公差
GENERAL TOLERANCE
X. X ±0.25
X. XX ±0.20
ANGLE ±1°



XR