

13790510059

5

4

3

2

1

4.00

0.12±0.02

1.40±0.25

1.42±0.25

A-A

0.53±0.15

C-C

1.05±0.2

B-B

0.88±0.2

0.27^{+0.12}_{-0.08}

4.70±0.30

2.10±0.25

D-D

EST1013 T P X - 2 X- X

↑ 普通代码+间距 ↑ T示端子 ↑ X普通脚 ↑ X普通 ↑ X公端
↑ 普通脚 ↑ L长 ↑ S短 ↑ U超薄 ↑ 示意90°
↑ 示意180°


P磷铜 0素材
B黄铜 2镀锡先冲后镀
E合金铜 3镀锡先镀后冲
 4镀全银(镀后冲)
 5G、15G示意镀金50"或150", 16示意镀金110"

SPECIFICATIONS

- Voltage rating:100V AC/DC;
- Current rating:1A AC/DC;
- Withstanding Voltage:500V AC/minute
- Temperature range:-20℃~+85℃
- Insulatin resistance:500MΩ Min
- Contact resistance:30mΩ Max
- Material:C5191
- After environmental testing:40 mΩ Max
- Wire range:#28~#32
- Insulation O.D.: 0.80mm Max

日期版次 REVISION	日 期 DATE	变更内容 DESCRIPTION	核 准 APPROVALBY

EST DGEASTOM 东莞市羿通实业有限公司 DONGGUAN EASTOM ELECTRONIC Co., Ltd.			
料号PART NO: EST1013TPX-2X-G			
品名 TITLE: 1013-T			
材料:	单位: MM	包装规格:	比例: 1:1
制图:	审核:	核准:	日期: 2025.07.11
			一般公差 GENERAL TOLERANCE X. X ±0.25 X. XX ±0.20 ANGLE ±1°



XR