

13790510059

5

4

3

2

1

 5.00 ± 0.20 0.15 ± 0.03 2.18 ± 0.30 0.73 ± 0.10 $\phi 1.50$ 1.95 ± 0.30 2.10 ± 0.25

sec:a-a

sec:b-b

 1.40 ± 0.25 1.20 ± 0.25

sec:b-b

 5.25 ± 0.30 8.50 ± 0.35 $-0.30^{+0.10}_{-0.05}$ 1.100

EST1503 T P X - 2 X- G

↑
羿通代码+间距

T示意端子

X普通脚

H高脚

E增高脚

P磷铜

B黄铜

E合金铜

X公端

G母端

C示意90°

S示意180°

0基材

2镀锡先冲后镀

3镀锡先镀后冲

5G、15G示意镀金50"或150"

1G示意镀金10"

■ SPECIFICATIONS

- Voltage rating: 250V AC/DC;
- Current rating: 1.5A AC/DC;
- Withstanding Voltage: 500V AC/minute
- Insulation resistance: 1000MΩ Min
- Temperature range: -20℃~+85℃
- Contact resistance: 20mΩ Max
- Material: C5191
- Wire size: AWG #24~#30

版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核准 APPROVAL BY



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号 PART NO: EST1503TPX-2X-G

品名 TITLE: MX1.5-T

材料: C5191

单位: MM

包装规格:

比例: 1:1

制图:


审核:

核准:

日期:

2022. 4. 19

一般公差
GENERAL TOLERANCE
X.X ±0.30
X.XX ±0.25
ANGLE ±1°



BR