



SECTION A-A

SECTION B-B



SECTION C-C



放大4倍SECTION D-D

EST2501 T P X - 2 X- X

羿通代码+间距

T示意端子

雄銅

黄铜

E合金铜

0素材

2. 镀锡先冲后镀

3 镀锡先镀后冲

5G、15G示意镀金5U"或15U",

1G示意镀金1U"

X公端
G母端

通	A 公端
	G 母端

1875-1876

Limitations


中后镀

度后冲

示意镀金50

金10”

一般公差	
GENERAL TOLERANCE	
X. X	± 0.30
X. XX	± 0.20
ANGLE	$\pm 5^\circ$



XJ

■ SPECIFICATIONS

- Voltage rating:250V AC/DC;
- Current rating:3A AC/DC;
- Withstanding Voltage:1000V AC/minute
- Insulatin resistance:1000M Ω Min
- Temperature range:-25℃~+85℃
- Contact resistance:20m Ω Max
- Wire size: AWG#22~#28

				料号PART NO: EST2501TBX-2X-X				一般公差 GENERAL TOLERANCE	
				品名 TITLE: XH2.5-T公				X.X ±0.30 X.XX ±0.20 ANGLE ±5°	
				材料: C2680	单位: MM	包装规格: 10K/卷	比例: 1:1	ANGLE ±5°	
日期版次 REVISION	日期 DATE	变更内容 DESCRIPTION	核 准 APPROVAL	制图: 胡宗显	审核: 金详富	核准: 李海平	日期: 2023/02/10		