

13790510059

5

4

3

2

 6.40 ± 0.15

a

b

 1.10 ± 0.08

a


b

 2.6 ± 0.25 2.4 ± 0.20

a-a SECTION

 2.0 ± 0.25 2.1 ± 0.20

b-b SECTION

 2.46 ± 0.25  $* 0.6^{+0.03}_{-0.05}$

c-c SECTION

 0.20 ± 0.03 1.28 ± 0.10 11.30 ± 0.30

Specifications :
Voltage rating: 250V AC / DC
Current rating: 5A Max AC / DC
Withstanding voltage: 1000V AC/minute
Temperature range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
Insulation resistance: $\geq 1000\text{M}\Omega$
Contact resistance: $\leq 10\text{m}\Omega$
After environmental testing: $\leq 20\text{m}\Omega$
Material: C5191
Plating: tin/gold
Wire size: #20-#24

EST3001 T P X - 2 X- G

羿通代码+间距

T示端子

X普通脚
H高脚
E增高脚X普通
L长
S短P磷铜
B黄铜
E合金铜0素材
2镀锡先冲后镀
3镀锡先镀后冲
5G、15G示意镀金5U"或15U"
1G示意镀金1U"

东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST3001TPX-2X-G

品名 TITLE: MX3.0-T(母)

材料: C5191

单位: MM

包装规格: 10K/卷

比例: 1:1

制图:


审核:

核准:

日期: 2022/07/26

日期版次
REVISION日期
DATE变更内容
DESCRIPTION核 准
APPROVALBY

一般公差
GENERAL TOLERANCE
X.X ± 0.30
X.XX ± 0.20
ANGLE $\pm 1^{\circ}$



EST OLD MODE