

$A \pm 0.35$

2.67

SECTION A-A

2.55

 $B \pm 0.40$

5.3

 16.95 ± 0.30

2.3

Model NO.	A	B
1*2P	3.0	7.0
1.3P	6.0	10.0
1*4P	9.0	13.0
1*5P	12.0	16.0
1*6P	15.0	19.0
1*7P	18.0	22.0
1*8P	21.0	25.0
1*9P	24.0	28.0
1*10P	27.0	31.0
1*11P	30.0	34.0
1*12P	33.0	37.0

EST3001 H - 1*NP X - B - X - HF-NK - X

↑
异通代码+间距↑
PIN数1示意单排
2示意双排B示意胶壳。
H后无数字默认材质V0
H后带数字2示意材质V2↑
X本色
B黑色
R红色
L蓝色
Y黄色
G绿色
C透明X普通
B带扣
C刺破
2L示意两侧带锁扣
U超薄
F母架型
HV带高凸点
LC带低凸点
K卡槽
E有耳↑
X公胶壳
G母胶壳↑
NO MARKHF示意无卤
NF普通含卤
A约热丝750
B约热丝850
X普通料

■ SPECIFICATIONS

- Voltage rating: 250V AC, DC
- Current rating: 5A, AC, DC
- Withstanding Voltage: 1500V AC/minute
- Insulation resistance: 1000MΩ min
- Temperature range: -25° C ~ +85° C
- HOUSING

- Part No.:
- Poles : 02-12P
- Housing Material: PA66 UL94V-2 Black
- The Dimension Marked " * " Must Testing

日期版次
REVISION日期
DATE变更内容
DESCRIPTION核 准
APPROVAL BY

制图:

审核:


核准:

日期:

2023/3/25

一般公差
GENERAL TOLERANCE

X. X	±0.30
X. XX	±0.20
ANGLE	±1°



东莞市羿通实业有限公司
DONGGUAN EASTOM ELECTRONIC Co., Ltd.

料号PART NO: EST3001H-1*NPB-X-G

品名 TITLE: MX3.0-H母 (无耳单排)

材料: pa66

单位: MM

包装规格: 1K/bag

比例: 1:1

制图:

审核:

核准:

日期:

2023/3/25

